

## Six burner Chinese range.

CC/06



Customized production only: both dimension and burners disposition are chosen by the client. Special stove for the oriental cooking with high performance burners: the vertical flame heats the pan uniformly, allowing a fast and complete cooking. Six burners can be chosen among: cast iron atmospheric burners with vertical flame (C KW 9,5 - T KW 14,0 - S KW 21,0) with gas safety valve taps, pilot flame and thermocouple. Pre-mixing radiant infra-red burner (B KW 23,0 110 Ac230V / 50Hz) with electronic flame control, adjustable flame 2 levels power KW 23,0 – KW 18,0. Removable burners to facilitate cleaning and maintenance. Structure in AISI 304 18/10 stainless steel AISI 304 18/10. Stainless steel cooking top thick 2,5 mm (reinforced): flat. Wall model. Removable drip-pans under the burners. Wok support rings (CERCHIO/CC) for C-T-S- B burners, built in black enamelled cast iron. Round grids (GRIGLIA/CC) for C-T-S burners built in black enamel cast iron. AISI 304 18/10 stainless steel adjustable legs. CE/IMQ conformity certification.

| TECHNICAL DATA                    |                                                                                                                                                       |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Larghezza                         | 1500 mm                                                                                                                                               |
| Profondità                        | 1000 mm                                                                                                                                               |
| Altezza                           | 850 mm                                                                                                                                                |
| Volume                            | 1,3 m3                                                                                                                                                |
| Peso                              | 214 Kg.                                                                                                                                               |
| Potenza Gas                       | A scelta tra / Choosing between / On peut choisir entre / Es posible elegir entre / 9,5 - 14,0 - 21,0 - 23,0 kW kW                                    |
| Brucciatori                       | 6                                                                                                                                                     |
| Combinazione Brucciatori          | A scelta tra / Choosing between / On peut choisir entre / Es posible elegir entre / 9,5 - 14,0 - 21,0 kW (no price difference) - 23,0 kW (extra cost) |
| Diametro                          | Model "C", "T" 175 mm, model "S" 220 mm, model "B" 150 mm                                                                                             |
| Padelle raccogli gocce estraibili | Si                                                                                                                                                    |

**FORHANDLER:**



**STORKØKKEN Udstyr**